

ALUMINUM FOIL TAPE 40 micron foil



DESCRIPTION

This aluminum foil tape is designed to be used in duct insulation. The tape offers good conformability, high holding power and long term performance. UL 723 listed. The tape comes with a liner.

MAIN FEATURES

- Listed UL 723 "Test for Surface Burning Characteristics of Building Materials"
- Good conformability
- High holding power
- Long term performance
- Good temperature resistance
- Good reflectivity of heat and light

APPLICATIONS

- Join and seal duct work
- Join and seal duct insulation
- Insulation boards and batts
- Seaming, sealing and patching of fiberglass duct board and other foil faced products

PERFORMANCE

HOLDING POWER

TECHNICAL DATA

Colour	Silver
Backing	40 micron (1.6 mil) Aluminum foil
Adhesive	Solvent based acrylic
Thickness	2.9 mil
Adhesion	75 oz/in
Tensile Strength.....	16 lb/in
Application Temperature	10°C to 40°C (50°F to 104°F)
Temperature Resistance	-20°C to 120°C (-4°F to 248°F)

Please note:

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness.

The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded.

No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.